DE

rail adjust
Montageanleitung

ACHTUNG:
Sie sind für die sichere und fachgerechte Anbringung des rail adjusts selbst verantwortlich. Eine sichere Anbringung der mitgelieferten Dübel und Schrauben kann nur bei der Anbringung in ungerissenem Beton empfohlen werden. Fragen Sie im Zweifelsfall einen Fachmann und lassen Sie sich entsprechend beraten!

Benötigtes Werkzeug:
- Bohrmaschine
- Bohrer 10 mm
- Gummi-Hammer
- Maulschlüssel SW13 oder TORX Tx40

Arbeitsschritte:
1. Den rail adjust an die Wandposition anhalten und die Bohrposition durch die Löcher für die Dübel markieren.
2. Löcher für Dübel in die Wand bohren.
   Durchmesser des Bohrers: Ø 10 mm
   Bohrlochtiefe: 70 mm
   Mindestverankerung: 50 mm
3. Dübel durch die Bohrungen in die gebohrten Löcher stecken, ggf. den Gummi-Hammer zu Hilfe nehmen.
4. Nun mit Maulschlüssel oder TORX die Schrauben in den vorher positionierten Dübeln verschrauben.



Abstand Boden - Unterkante rail adjust: 30 cm



Der Aufnahme-Pin muss frei beweglich sein.

Das Feststellrad muss sich auf der rechten Seite befinden.



Fragen? Ruf uns an. 02234 9895290.

© aerobis fitness GmbH 2016.

EN

rail adjust
Installation instructions

ATTENTION:
You are solely responsible for a correct installation of the rail adjust. A safe installation with the included screws and dowels can only be advised in non-cracked concrete. In case of doubt please contact an expert for a consultation on your specific requirements!

Required tools:
- Drill
- Drill bit 10 mm
- Rubber hammer
- Spanner SW13 or TORX Tx40

Work steps:
1. Put the rail adjust against the wall and mark the holes for the drilling position of the dowels.
2. Drill the holes for the dowels into the wall.
   Diameter of the bit: Ø 10 mm
   Hole depth: 70 mm
   Minimum anchorage: 50 mm
3. Put each dowel into the respective opening in the and then put the dowels into the holes.
4. Now bolt the rail adjust with the screws in the previously positioned dowels.



Distance floor - lower edge rail adjust:
30 cm / 12“



The attachment pin must be able to move freely.

The locking wheel must be on the right side.



Questions? Call us. +49 2234 9895290.

© aerobis fitness GmbH 2016.